

RICHMOND

LPS 1673 Doorset Range

Timber Security Doorsets

+44 (0)1234 826 316 - sales@staffordbridge.com



Typical Installation

EXAMPLE LOCKING FINISHES



CE External doorsets are CE marked to EN14351-1:200 + A1:2010

For further information and latest copies of the DoP's (Declaration of Performance), visit our website at www.staffordbridge.com/technical

The RICHMOND doorset has been developed to resist violent forced entry attempts, delay security breaches and protect both people and valuable assets from violent, fast-moving attacks using bladed and blunt-impact weapons when installed in designated safe spaces.

LPS 1673 tool kits include: sledgehammers, knives, machetes, bolt cutters, hammers and crowbars. Performance tests using these tools simulate marauding terrorist attacks (MTAs) and determined forced entry attempts to ensure the doorset's resilience.

DETAILS

DOORSET TYPE (SUITABLE FOR INTERNAL & EXTERNAL USE)

- Timber doorset, inward or outward opening

LOCKING SYSTEM

- Surface-mounted or mortice-fitted systems available, all as tested and certified
- Refer to full certification for complete approved locking list

OPTIONAL ENHANCEMENTS

- Glazed doorset
- Drop seal and kick plate
- Closers/operators
- Kick plates
- Aluminum thresholds
- Hardwood sills

FINISHES

Our doors are designed to seamlessly combine high security with bespoke aesthetics. The Richmond is available in a range of timber, glazed and heritage finishes. Whether you're looking to match your existing interior or create a new build, the Richmond can be tailored to meet your specific requirements. Our customisable designs provide aesthetically pleasing solutions suitable for all applications.

PERFORMANCE OPTIONS

SECURITY RESISTANCE

- LPS 1673 A, B, C, D tool kits for up to 300 seconds

ACOUSTIC RESISTANCE

- 35 dB, please contact our sales team to discuss requirements

FIRE RESISTANCE

- Up to FD60 on a single doorset, please contact our sales team to discuss requirements

	Richmond Doorset Range: Approved Locking Systems*											
Delay Time	Surface-mounted single-point				Mortice-fitted single-point				Mortice-fitted multi-point			
300 SECS												
240 SECS												
180 SECS												
120 SECS												
60 SECS												
30 SECS												
	A	B	C	D	A	B	C	D	A	B	C	D
	Tool Category											

NB: LPS 1673 certification may not cover some elements of the enhanced performance options. Please call our technical department for further information.

*Lock and door specification differs based on rating chosen.



Securing the people who secure the country

